

Technical Data Sheet

NewPro Adhesion Promoter for Non-Porous Surfaces as Sealer / Primer for NewPro Graffiti Magic Matt & Gloss

Product description:	NewPro Water Based Primer as an Adhesion Promoter for Non-Porous Surfaces. A universal with water dilutable adhesive primer with light corrosion inhibition properties.
Most important properties:	prevents rust, scratch-, and wear proof, insulation layer on Medium Density Fibreboard (MDF) excellent suture and easy apply.
Applications:	on glass, tiles, wood, synthetic materials, various metals and powder coated undergrounds if in doubt first apply to attest surface.
Product information:	Binder, acrylate dispersion, Resin: matt
Density:	1,10 kg/litre
Theoretical Efficiency:	10-15 m ² per litre at 75 µm wet layer thickness
Tenability:	approx. 12 months in unused packing
Conservable:	keep cool and away from frost
Processing:	By brush, roller and spray
Drying at 20°C :	after 1 hour
Processing Conditions:	after approx.. 1-2 hours with several paint systems and water soluble and solvent containing products repaint able depending on the relative humidity.
Dilution:	maximal 10% with water
Cleaning materials:	immediately with luke warm water
Pretreatment:	remove inferior paint layers underground must be dry, clean and greaseproof sandpaper surface and degrease with water based cleaner, galvanized surfaces sandpaper mechanically and degrease with thinner, immediately apply NewPro Adhesion Promoter. NewPro Adhesion Promoter is not too thin layers due to the fact this can negatively influence the primer.
Health And Safety	Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of Water or recognized cleanser. Keep out of reach of children. Safety data sheet available on request.

Read carefully:

The information on this data sheet is based on the current status of technical development as well as our experience with the product. However, given the variety of surfaces and ambient conditions, the information provided on this data sheet shall in no way diminish the responsibility of the user to ensure with due care, that our product is suited for the intended purpose, surface and application conditions.

Since application and processing lie outside our purview, no manufacturer liability shall be derived from the information provided herein. Our General Terms and Conditions of business shall apply in all cases.

All information is subject to change without notice.

14.09.2014