

Product Data Sheet

NewPro Parking Bay Marking Paint

Product Description

NewPro produces an environmentally friendly; water based and solvent-free Marking Paint for use in indoor and outdoor areas.

NewPro-Marking Paint offers very good processing properties and provides long term durability after two to three applications. Optimal adhesion properties are shown by the product on nearly every standard surface such as: tar, concrete, screed and paving.

NewPro-Reflex pearls) can be sprinkled onto the fresh paint coating to increase reflection and traction properties.



Application Possibilities

NewPro-Marking Paint is designed for outdoor use but is it equally suitable for indoor areas.



It can be used in the following areas:

- Parking Lots
- Multi-Storey Car Parks
- Underground Car Parks
- Internal Company Road Marking
- Escape Routes
- Pedestrian Crossings
- Boundary Lines

Product Details:

Article Number

white = PM1 – 600
yellow = PM2 – 600
red = PM3 – 600



Material Type:

Weather resistant according to DIN 18363 - A. 3. 1. 10.

EU-Limit for this product (Cat. Ale)

130 g/l (2010) This product contains a maximum of 10 g/l VOC

Characteristics:

Water thinnable, high-coverage marking paint, diffusion permeable, elastic, hydrophobised and quick-drying.

Colour Shades: White, yellow, red.

Coverage: 0.2 – 0.4 kg/ m² /Coating

Processing Temperature: > 10°C

Drying: The next coat can be applied after overnight drying.

Storage: Cool and dry but frost-free.