

Directions for Use
NewPro Nano TEX NA 153
Textile Impregnation

NewPro Nano TEX NA 153 is a hydrophobic surface impregnation based on chemical nanotechnology. The impregnation forms a transparent and ultra thin layer on absorbent textile surfaces and shows oil and water repelling properties.

For best results, proceed as described below:

1. Cleaning

The surface to be treated must be free of dust and pollution to ensure the best impregnation performance and durability.

2. Application of NewPro Nano TEX NA 153

NewPro Nano TEX NA 153 has to be applied by spraying. Apply evenly but sparingly to the surface. Consumption depends on substrate absorption.

3. Drying

The substrate has to be dried at room temperature. Avoid drying at higher temperatures because of possible forming of explosive mixings with air.

4. Cleaning of treated surfaces

Surfaces treated with NewPro Nano TEX NA 153 can be cleaned easily with water.

Read carefully:

The information on this data sheet is based on the current status of technical development as well as our experience with the product. However, given the variety of surfaces and ambient conditions, the information provided on this data sheet shall in no way diminish the responsibility of the user to ensure with due care, that our product is suited for the intended purpose, surface and application conditions. Note in particular, that we accept no liability in cases where we have not explicitly stated application purposes and types of use.

All information and advices given in the security data sheet must be considered anyway.