

Product Data Sheet

NewPro Graffiti Remover PLUS Nanotech

NewPro Graffiti Remover PLUS removes scribbling from walls easily. NewPro Graffiti Remover PLUS is an efficient graffiti remover based on nanotechnology. Its novel properties allow for fast and clear removal of paint from surface, without smearing or formation of shades as is often the case with conventional graffiti removers.

NewPro Graffiti Remover Plus removes spray paints, paint stick as well as all kinds of felt pens. It is applicable to mineral sub-surfaces like glass, metal, wood, 2-component lacquer, enamel, polyethylene (PE), and polystyrene (PS). Application on other sub-surfaces should be tested at an inconspicuous area.

Advice: drawn-in paint on absorbent sub-surface (concrete, sandstone) can be activated with NewPro Cleaner New – saturate absorbent sub-surface with NewPro Cleaner NEW and afterwards treat with NewPro Graffiti Remover Plus.

NewPro Graffiti Remover PLUS contains ingredients based on renewable raw materials; with the addition of water it is bio-degradable; it does not contain halogenated or toxic solvents.

NewPro Graffiti Remover PLUS is ready-to-use gel. If shaken strongly it will become capable of flowing and can be extracted easily from container without running down on the wall. Required are approx. 0.1-0.4 l/m² depending on sub-surface and degree of soiling.

Storage life 1 year minimum.

Handling instructions:

- 1) Sub-surface must be dry. Apply NewPro Graffiti Remover PLUS undiluted with brush or roller. Spread thoroughly too rough and old sub-surfaces. Massage NewPro Graffiti Remover PLUS with circling brush strokes for complete penetration into the pores.
- 2) NewPro Graffiti Remover PLUS should affect structure approx. 2-10 minutes, until graffiti paint can be rubbed off sub-surface. The time depends on the kind and age of the graffiti paint, the sub-surface, as well as temperature (best with temperatures between 10° and 25°C) Do not let touch dry (in case of strong wind or solar radiation, cover with foil with processing).
- 3) Important: Pick up soaked foil with moist sponge or moist brush (see hint) and rub off surface. NewPro Graffiti Remover PLUS becomes cleaning foam removing graffiti paint from sub-surface. (2 step effect)
- 4) Rinse well with water. Use pressure sprayer or high-pressure cleaner for porous surfaces. Attention: the surface may be damaged if the pressure or temperature is too high.

If paint residues remain, repeat process for the affected areas after drying. If the sub-surface had a coat of paint, this might be dissolved as well in some cases. The area needs to be newly painted after the graffiti removal.

HINT: Smooth surfaces (plastic, glazed tiles, polished natural stone, etc) should be treated using a moist cloth or fine pored sponge, porous sub-surfaces like plaster, limestone, sandstone, and concrete should be treated with brush or hard sponge.

NewPro – New Products & Innovative Ideas for Surfaces
Lutz-Henning Robitzsch
Ricarda-Huch-Weg 2 D-40789 Monheim a. Rhein
Tel: +49 (0) 2173/964280 Fax: +49 (0) 2173/964282
eMail: news@newpro.de Internet: www.g-pro.com

GRAFFITI
MAGIC



NewPro Graffiti Remover PLUS is biodegradable. However, it is advisable to absorb paint remains using fleece. Please observe legal regulations.

Rinse brushes with water immediately after use.

Advice: wear protective clothing, protective gloves and goggles.

Xi: In case of skin contact, rinse thoroughly with water and soap. In case of eye contact, rinse eye for several minutes under water jet. If swallowed drink plenty of water and consult physician. Do not induce vomiting.

Dispose of remains according to legal regulations. Recycle containers only if completely empty.