

Product Data Sheet

NewPro Graffiti Protection C Sacrificial (Temporary)

Product Description

NewPro Graffiti Protection C Sacrificial is a preliminary protective layer for areas threatened by graffiti attacks. This protective layer is based on a special wax and avoids permeation of paint into the surface. Due to the innovative mode of action the security layer absorbs less dirt than conventional wax-based products. Additionally, the treated surface becomes water-repellent but stays vapour permeable so that damages to the building fabric can be prevented.

NewPro Graffiti Protection C Sacrificial is invisible as well as UV and weather resistant. The layer can be applied on painted as well as unpainted surfaces such as concrete, plaster, bricks and other mineral surfaces. Due to its matting properties **NewPro Graffiti Protection C Sacrificial** is not suitable for glossy surfaces such as glass or metal.

NewPro Graffiti Protection C Sacrificial is liquid and ready to use. Depending on the surface use approx. 0,1 l/m² - 0,4 l/m².

NewPro Graffiti Protection C Sacrificial is intended for industrial use, should not be exposed to temperatures below 0 °C and may be stored for 36 months from the date of production (see label). Storage beyond the date indicated on the label does not necessarily imply impracticality of the product.

According to E(directives or the respective national laws **NewPro Graffiti Protection C Sacrificial** is not subject to specific labelling.

IMPORTANT NOTES

We recommend the use of working clothes and .safety goggles!

Protect from freezing!

Please follow the instructions in the safety data sheet according to professional use, storing and disposal!

GUIDE TO USE

Application

Before applying the protective layer the surface needs to be cleaned from existing graffiti and dirt, if applicable. The surface should be dry and cleaned from loose dirt, moss and algae.

NewPro Graffiti Protection C Sacrificial should be stirred thoroughly and applied undiluted and evenly on the surface. Depending on the surface, a sponge, a brush, a paint roller or a pressure sprayer can be used for this purpose.

Please Note

In case of extremely porous or absorbent surfaces we recommend to apply **NewPro Graffiti Protection C Sacrificial** twice (intermediate drying process: 30 minutes).

Use **NewPro Graffiti Protection C Sacrificial** only when outside temperature is above 5 °C!

NewPro Graffiti Protection C Sacrificial protective layer is fully functional after one hour and lasts for at least one year.

Removal

The protective layer can be simply removed together with the graffiti using hot water (>80 °C). We recommend the use of a steam or a high pressure cleaner. Warning: Use only low water pressure to avoid damage to the surface! Alternativ kann die Schutzschicht auch mit heißem Wasser und einer Bürste entfernt werden.

If the use of hot water is not applicable, the graffiti can be removed with the special cleaning agent **NewPro Remover for temporary surfaces** and cold water.

After the cleaning process **NewPro Graffiti Protection C Sacrificial** is applied again. According to statistical data spray paint vandals lose their interest after a surface is being cleaned approx. four times successively.

NOTE

Paint smearing can be removed quickly with **NewPro Graffiti Protection C Sacrificial** graffiti-remover without smearing and formation of shades – being usually a common result of conventional products.

Surfaces that are polluted unsightly through particulate matter, soot and fat can be cleaned deep-down with **NewPro Remover Plus**. Due to its innovative mode of action treated surfaces are stain-resistant throughout several months.