

Product Data Sheet

NewPro-Nano HighEnd Polish

- Maintains Laquer on Light Coloured Cars

Product Description

NewPro-HighEnd Polish is a solvent containing lacquer sealant based on chemical nano-technology. The polish produces a transparent ultra thin layer, which rejuvenates the shine in the lacquer in paints, protects and gives the surface a long-lasting pearl-off effect. The water and dirt/grime repellent sealant with Easy-2-Clean-Effect® offers a beautifying and simple cleaning of vehicles.

Range of Application and Use

Suitable Surfaces:

- Automobile lacquered surfaces.

Unsuitable Surfaces:

- Rubber parts
- Unlacquered or raw synthetic material surfaces.

Technical Characteristics

Material Basis:

- Composite material on a solvent basis with wax additives.

Viscosity:

- < 102 mPas (DIN 53214).

Instruction for Application and Use

Surface pre-treatment:

Thoroughly pre-clean the surface. The surface must be free of dirt, dust, and grime and must be dry.

Application/Use:

Shake well before using. Polish out with a towel or with a polishing machine and apply sparingly in portioned surface areas, rub in and shortly after airing out the solvent, polish out.

Cleaning of the sealed surface:

Dirt, grime and dry remains can be removed with a moist towel. Do not apply high water pressure when washing cars neither hot steam spray. Solvent-based cleaners should not be used.

NewPro – New Products & Innovative Ideas for Surfaces
Lutz-Henning Robitzsch
Ricarda-Huch-Weg 2 D-40789 Monheim a. Rhein
Tel: +49 (0) 2173/964280 Fax: +49 (0) 2173/964282
eMail: news@newpro.de Internet: www.g-pro.com

**GRAFFITI
MAGIC**



Improvement and new coatings:
Can be newly applied to clean and dry surfaces as described above.

Instruction for Application and Use

Use:

- Approximately 2 – 5 ml per square meter
- Maschine application 50-60ml / car
- Application by hand 150 ml / car.

Required Conditions for Use/Application

Application can be effectuated with a air and surface temperature between a min. +10° Celsius and max. +25° Celsius. Ensure proper ventilation.

Cleaning of tools:

- Not applicable / Wipe polish residue with petroleum spirit.

Drying:

- The sealant is dry after polishing.

During the drying period, protect the coated surface from grease, moisture and cleaning solvents.

Delivery Form

Packaging sizes:

- By arrangement.

Color:

- Milky white liquid.

Further Instructions

Storage:

- Protect against moisture, frost, and heat
- Storable for up to 12 months when stored at room temperature in tightly sealed original packaging.

Disposal:

- Dispose of product remains at an officially designated disposal site
- Only recycle completely emptied containers
- Surplus (left-over) product can be disposed according EWC (European Waste Code) 080105 (cured paints and lacquers) or household waste.

Protective Measures

Follow the instructions and the safety precautions on the product label before and during use. We advise to take standard safety and protective measures when working with chemicals. After working with product, wash hands thoroughly. Keep out of reach of children. For more detailed instructions and information see the product safety data sheet.

Important notice

This technical information is based on the latest standard of technology combined with our experience. Taking into consideration the variety of surfaces and object surface conditions, the user is not relieved of the responsibility and obligation to carry out tests with our products by qualified specialists to determine the suitability of the product(s) for their intended purpose and use. Because application and use are beyond our influence, the contents of the technical data sheets do not imply to the manufacturer's and seller's liability. In any case, our general business terms and conditions apply. In the event of a subsequent publication of this technical data sheet, the information in this data sheet becomes invalid.

For further instructions, cautions or notice, please refer to the product safety data sheets. In case of a reprint this information will become invalid.